




More information on the website  
[radwag.com/us/info,w1,07Z](http://radwag.com/us/info,w1,07Z)

# WPY 60/C3 Multifunctional Scale



The drawings, photos and graphics used are for illustrative purposes only.

## Functions

-  Dosing
-  Labelling
-  Plus/Minus Control
-  Percent Weighing
-  Totalizing
-  Parts counting
-  Peak hold
-  Formulation
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  IR sensors
-  Animal weighing
-  Differential weighing
-  ALIBI Memory

## Datasheet

|  |        |
|--|--------|
| Maximum capacity [Max]                 | 60 kg  |
| Minimum load                           | 400 g  |
| Readability [d]                        | 20 g   |
| Tare range                             | -60 kg |
| Max readability for non-verified scale | 2 g    |
| Stabilization time                     | 3 s    |

|                                |   |
|--------------------------------|---|
| Adjustment                     | external  |
| OIML Class                     | III   |
| <b>Physical parameters</b>     |   |
| Display                        | 5,7" Resistiv-Farb-Touchscreen                            |
| Weighing pan dimensions        | 500x700 mm  |
| Packaging dimensions           | 730x800x270 mm  |
| Net weight                     | 21,7 kg   |
| Gross weight                   | 25,5 kg   |
| <b>Construction</b>            |   |
| Protection class               | IP 43   |
| <b>Communication interface</b> |   |
| Communication interface        | 2xRS232, 2xUSB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi |
| <b>Power supply</b>            |   |
| Power supply                   | 100 – 240 V AC 50/60 Hz                                   |
| <b>Operating temperature</b>   |   |
| Operating temperature          | -10 ÷ +40 °C  |

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



## Accessories

Transponder card readers  
 RS 232 cables (scale - printer)  
 Cigarette lighter receptacle power supply cables  
 Barcode scanners  
 RS 232, RS 485 cables  
 Label Printers  
 Antivibration tables  
 Displays  
 IN/OUT Cables


Keypad, external switches  
 Stands, wall mounting kits and mounting brackets  
 Receipt Printer  
 F1 Mass Standard - knob weights without adjustment chamber, set  
 AP2-1 Current Loop Unit  
 RS 232, RS 485 cables  
 Additional Weighing platforms Module  
 RS 232 – USB Converter  
 RS 232 cables (scale - printer)

## Software

- E2R Weighing [WX-010-0099]
- E2R PGC [WX-010-0051]
- RAD Key [WX-010-0005]
- Label Editor R02 [WX-010-0094]
- Scale Editor - EWAG 2.1 [WX-010-0173]

- E2R Formulations [WX-010-0043]
- E2R Weighing Records [WX-010-0038]
- Audit Trail Reader [WX-010-0186]
- RADWAG Remote Desktop [WX-010-0107]
- RADWAG Development Studio [WX-010-0104]

## Device dimensions



WPY C3/M

---