



More information on the website
radwag.com/br/info,w1,140

Terminal de Pesagem PUE CY10

WX-008-0217



The drawings, photos and graphics used are for illustrative purposes only.

Funções



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit
measurement



Statistics



Checkweighing



IR sensors



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Differential weighing



Ambient conditions
monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

Ficha Técnica

Physical parameters

Display

10" graphic colour touchscreen

Construção	
Protection class	IP 43
Housing	ABS + aluminium
Interface de comunicação	
Interface de comunicação	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	12 – 15 V DC
Consumo de energia	1 A
Metrological parameters	
Quantidade máxima de unidades de verificação	10000
Voltagem mínima por unidade de verificação	0,4 μ V
Tensão máxima por unidade de verificação	3,25 μ V
Impedância mínima da célula de carga	50 Ω
Impedância máxima da célula de carga	1200 Ω
Load cell excitation voltage	5V
Aumento máximo up to sinal	19,5 mV
Connection of load cells	4 or 6 wires + shield
Environmental conditions	
Operating temperature	-10 – +40 °C
Components and software	
Operating system	Linux
Processor	quad-core Broadcom 1,5 GHz
Memory	16 GB, 2GB RAM
Multiple range	YES
Características de uso	
Número máximo de plataformas	max.2

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Additional fee for verification



Device dimensions

