



More information on the website  
[radwag.com/en/info,w1,2FA](http://radwag.com/en/info,w1,2FA)

# MAS 220.Y Weighing Module



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Metrological parameters	
Maximum capacity [Max]	220 g
Readability [d]	0.1 mg
Tare range	-220 g
Physical parameters	
Display	5.7" resistive colour touchscreen
Weighing pan dimensions	ø42 mm
Device dimensions	175×236×105 mm
Packaging dimensions	610×340×295 mm
Net weight	3.7 kg
Communication interface	
Communication interface	2×RS232, 2×USB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz

## Environmental conditions

Operating temperature	+10 – +40 °C
Relative humidity	40% – 80%

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories

Antivibration Tables  
Professional Weighing Tables  
RS 232, RS 485 cables

RS 232 – USB Converter  
RS 232 cables (scale - printer)

## Software

• RAD Key [WX-010-0005]  
• R-Lab [WX-010-0080]

• R-Panel [WX-010-0187]  
• RADWAG Development Studio [WX-010-0104]

## Device dimensions

