



More information on the website
radwag.com/ja/info,w1,519

XA 110.5Y.A

WL-110-0002



The drawings, photos and graphics used are for illustrative purposes only.



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit measurement



Statistics



Checkweighing



IR sensors



Under-pan weighing



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Automatic sliding door



Density determination



Differential weighing



Ambient conditions monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi



XXXXXXXX

XXXXXXXX [Max]

110 g

XXXX

1 mg

Wzrost	
Wzrost [d]	0,01 mg
Waga [e]	1 mg
Wzrost	-110 g
Wzrost [5% Max]	0,005 mg
Wzrost [Max]	0,02 mg
Wzrost (USP)	10 mg
Wzrost (U=1%, k=2)	1 mg
Wzrost [5% Max]	0,012 mg
Wzrost [Max]	0,03 mg
Wzrost	±0,06 mg
Wzrost	0,06 mg
Wzrost	$1 \times 10^{-6} 700 \text{ mA} - 1 \text{ A} \times \text{Rt}$
Wzrost	4 s
Wzrost	Wzrost (Wzrost)
OIML	I
Wzrost	
Wzrost	20
Wzrost	10" Wzrost + Wzrost Wzrost
Wzrost	Wzrost
Wzrost
Wzrost	200×170×220 mm
Wzrost	ø90 Wzrost + ø85 Wzrost mm
Wzrost	750×492×595 mm
Wzrost	14,7 kg
Wzrost	16 kg
Wzrost	
Wzrost	IP 43
Wzrost	
Wzrost	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Wzrost	
Wzrost	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A : 12 – 15V DC 1,6A max*
Wzrost	
Wzrost	+10 – +40 °C
Wzrost	±0,3 °C / 1 h (±1 °C / 8 h)
Wzrost	20% – 80%
Wzrost	±1% / h (±4% / 8 h)

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.

❏❏❏❏❏ (Additional Fee)

❏❏❏❏❏❏
 RFID❏
 ❏❏❏
 ❏❏❏❏❏❏❏❏
 ❏❏❏❏❏
 ❏❏❏❏❏
 RS 232❏RS 485 ❏❏❏
 ❏❏❏❏❏❏❏❏
 ❏❏❏❏❏
 ❏❏❏❏❏❏❏❏
 ❏❏❏❏❏❏❏
 ❏❏❏❏❏❏❏

❏❏❏❏❏❏
 ❏❏❏❏❏❏
 THBR 2.0 ❏❏❏❏ - ❏❏❏❏ - ❏❏❏❏❏❏❏❏
 RS 232❏RS 485 ❏❏❏
 ❏❏❏❏❏❏
 XA 4Y❏❏XA 5Y❏❏❏❏❏❏❏❏❏❏
 ❏❏❏
 ❏❏❏❏❏❏❏❏❏❏❏
 ❏❏❏❏❏❏
 ❏❏❏❏❏
 RS 232 – USB ❏❏❏❏
 ❏❏❏❏❏❏❏

❏❏❏❏❏ (Additional Fee)

- [WX-010-0099]
- [WX-010-0005]
- [WX-010-0107]
- [WX-010-0173]

- [WX-010-0038]
- [WX-010-0094]
- [WX-010-0080]
- [WX-010-0104]

❏❏❏❏❏❏

