



More information on the website
radwag.com/ja/info,w1,5I9

XA 110.5Y.A

WL-110-0002



The drawings, photos and graphics used are for illustrative purposes only.

- | | | | |
|------------------------|-----------------------|-------------------------------|-----------------------------|
| Autotest | Dosing | Percent Weighing | Parts counting |
| Peak hold | Formulation | Newton unit measurement | Statistics |
| Checkweighing | IR sensors | Under-pan weighing | GLP Procedures |
| Animal weighing | Pipettes Calibration | Air density correction | Automatic sliding door |
| Density determination | Differential weighing | Ambient conditions monitoring | Statistical Quality Control |
| Packaged Goods Control | ALIBI Memory | Wi-Fi | |

[Max]

110 g

1 mg

Wzrost	
Wzrost [d]	0,01 mg
Waga [e]	1 mg
Wzrost	-110 g
Wzrost [5% Max]	0,005 mg
Wzrost [Max]	0,02 mg
Wzrost (USP)	10 mg
Wzrost (U=1%, k=2)	1 mg
Wzrost [5% Max]	0,012 mg
Wzrost [Max]	0,03 mg
Wzrost	±0,06 mg
Wzrost	0,06 mg
Wzrost	$1 \times 10^{-6} 700 \text{ mA} \times \text{Rt} - 1 \text{ A} \times \text{Rt}$
Wzrost	4 s
Wzrost	Wzrost (Wzrost)
OIML	I
Wzrost	
Wzrost	20
Wzrost	10" Wzrost + Wzrost Wzrost
Wzrost	Wzrost
Wzrost
Wzrost	200×170×220 mm
Wzrost	ø90 Wzrost + ø85 Wzrost mm
Wzrost	750×492×595 mm
Wzrost	14,7 kg
Wzrost	16 kg
Wzrost	
Wzrost	IP 43
Wzrost	
Wzrost	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Wzrost	
Wzrost	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A : 12 – 15V DC 1,6A max*
Wzrost	
Wzrost	+10 – +40 °C
Wzrost	±0,3 °C / 1 h (±1 °C / 8 h)
Wzrost	20% – 80%
Wzrost	±1% / h (±4% / 8 h)

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.

