



More information on the website
radwag.com/en/info,w1,8J8

UMA 2.5Y.FC Automatic Weighing System



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Metrological parameters	
Maximum capacity [Max]	2.1 g
Readability [d]	1 µg
Tare range	-2.1 g
Repeatability (Max)	1 - 2 µg
Repeatability low load	0.5
Linearity	≤ 1.5 µg
Stabilization time	30 s
Adjustment	internal (automatic)
Physical parameters	
Display	10" graphic colour touchscreen
Magazine positions	24 filtrów
Weighing pan dimensions	ø20 mm
Device dimensions	900×535×585 mm

Communication interface	
Communication interface	2×RS232, 2×USB-A, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz
Environmental conditions	
Operating temperature	+19 ÷ +25 °C
Storage temperature	-20 ÷ +50 °C
Operating temperature change rate	±0.5°C/12h (±0.3°C/4h)
Relative humidity	40% – 60%
Relative humidity change rate	± 2 % / 4 h

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.




Accessories



RFID Tags
 Additional modules
 Protective cover for balances

RS 232, RS 485 cables
 Receipt Printer
 Fingerprint Reader

Device dimensions



UMA-100, UMA-1000



UMA-control unit



UMA-5

