

CY10.6.D2.K.M3 Multifunctional Scale



More information on the website radwag.com/us/info,w1,90G



The drawings, photos and graphics used are for illustrative purposes only.

Functions

Autotest

Peak hold

Checkweighing

Pipettes Calibration

Ambient conditions monitoring

Wi-Fi

Dosing

Formulation

IR sensors

Air density correction

Statistical Quality Control

Density determination

Packaged Goods Control

Percent Weighing

Newton unit

measurement

GLP Procedures

Animal weighing Differential weighing

Parts counting

Statistics


ALIBI Memory

Datasheet

Maximum capacity [Max]	6 kg	
Minimum load	40 g	
Readability [d]	2 g	

Verification unit [e]	2 g
Tare range	-6 kg
Max readability for non-verified scale	0,2 g
Stabilization time	2 s
Adjustment	external
OIML Class	III
Physical parameters	
Leveling system	manual
Display	10" graphic colour touchscreen
Weighing pan dimensions	195×195 mm
Packaging dimensions	530×310×150 mm
Net weight	3,7 kg
Gross weight	4,6 kg
Cable length	1 m
Multiple range	YES
Construction	
Protection class	IP 43
Housing	steel + ABS
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Power supply	12÷15V DC
Power consumption	1A
Operating temperature	-10 ÷ +40 °C
Storage temperature	-25 ÷ +70 °C
Features of use	
Max number of platforms	max.2

^{*} Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

MediaBox Mild steel powder coated weighing platforms RFID Tags Power Adapters Additional Weighing platforms Module Mild steel powder coated weighing platforms Additional modules Platforms in plastic casing Protective cover for balances Barcode scanners Label Printers RS 232, RS 485 cables Fingerprint Reader RS 232 – USB Converter Receipt Printer

Software

- E2R Weighing [WX-010-0099] RAD Key [WX-010-0005]
- RADWAG Remote Desktop [WX-010-0107]

- E2R Weighing Records [WX-010-0038] Label Editor R02 [WX-010-0094] Scale Editor EWAG 2.1 [WX-010-0173]