

CY10.30.C3.K.M3 Multifunctional Scale

WP-125-0039





The drawings, photos and graphics used are for illustrative purposes only.

Functions



Dosing

Wi-Fi



Percent Weighing



Parts counting



Peak hold



Formulation



IR sensors



Animal weighing



SOC Statistical Quality Control



Adjustment

Datasheet

Maximum capacity [Max] 30 kg Minimum load 200 g Readability [d] 10 g Verification unit [e] 10 g -30 kg Tare range Max readability for non-verified scale 1 g Stabilization time 3 s

external

OIML Class	III
Physical parameters	
Leveling system	manual
Display	10" graphic colour touchscreen
Cable length	2,5 m
Weighing pan dimensions	500×700 mm
Packaging dimensions	850×800×270 mm
Net weight	22,7 kg
Gross weight	26,5 kg
Construction	
Protection class	IP 65 construction, IP 43 terminal
Housing	steel + ABS
Communication interface	2×USB-A, USB-C, RS 232 (COM3), HDMI, Ethernet, Wi-Fi, Hotspot
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A Balance: 12 – 15V DC 1,6A max; 10–19W*
Operating temperature	-10 - +40 °C
Storage temperature	-25 - +70 °C
Multiple range	YES
Features of use	
Max number of platforms	max.2

^{*} Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories (Additional Fee)

MediaBox
Mild steel powder coated weighing platforms
RFID Tags
Power Adapters
Additional Weighing platforms Module
Mild steel powder coated weighing platforms
Additional modules
Platforms in plastic casing

Protective cover for balances
Barcode scanners
Label Printers
RS 232, RS 485 cables
Stands, wall mounting kits and mounting brackets
Fingerprint Reader
RS 232 – USB Converter
Receipt Printer

Software (Additional Fee)

- E2R Weighing [WX-010-0099]
- RAD Key [WX-010-0005]
- RADWAG Remote Desktop [WX-010-0107]

- E2R Weighing Records [WX-010-0038]
- Label Editor R02 [WX-010-0094]
- Scale Editor EWAG 2.1 [WX-010-0173]

Device dimensions

