



More information on the website
radwag.com/tr/info,w1,C6W

HX5.EX-1.4.3000.C11 4 Yk Hcreli Platform Terazi



The drawings, photos and graphics used are for illustrative purposes only.

Fonksiyonlar



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit
measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

Teknik Veriler

Metrolojik parametreler

Maksimum yk [Max]	3000 kg
Minimum yk [Min]	20 kg
Okuma iinruluu [d]	1000 g
Dara aralığı	-3000 kg

Fiziksel parametreler

Display	5" grafik renkli
Kablo uzunluu	3 m

Fiziksel parametreler	
Tartım kefesi boyutları	2000×2000 mm
Net ağırlık	297,8 kg
Brüt ağırlık	298 kg
Konstrüksiyon	
IP Sınıfı	IP 65 konstrüksiyon, IP 66/68 terminal
Konstrüksiyon	toz kaplı çelik St3S
Sertifikasyon ATEX	II 2G Ex ib IIB T4 Gb
Sertifikasyon IECEx	Ex ib IIB T4 Gb
İndikatör	PUE HX5.EX-1
Haberleşme arayüzler	
Haberleşme arayüzü	2×RS232, RS485
Elektrik parametreleri	
Güç kaynağı	100 – 240 V AC 50/60 Hz
Maksimum güç tüketimi	15 W
Çevresel koşullar	
Çalıştırma sıcaklığı	-10 – +40 °C
Atmosferik nem	10% – 85% RH yoğunlaşma yok



Extra payment for verification



Aksesuarlar

Haberleşme modülü
Terazi için tasarlanmış kendinden korumalı güç kaynağı

Fiş yazıcı

Yazılım

- E2R Tartım [WX-010-0099]
- RAD Key [WX-010-0005]
- Alibi Okuyucu PC Yazılımı [WX-010-0114]
- Terazi Editörü - EWAG 2.1 [WX-010-0173]

- E2R Tartı Kayıtları [WX-010-0038]
- Etiket Editörü R02 [WX-010-0094]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]