



More information on the website
radwag.com/en/info,w1,CJ1

CY10.150/300.C2.K.M3 Multifunctional Scale



The drawings, photos and graphics used are for illustrative purposes only.

Functions



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



IR sensors



Animal weighing



Statistical Quality Control



Wi-Fi

Datasheet

Metrological parameters	
Maximum capacity [Max]	150/300 kg
Minimum load	1000 g
Readability [d]	50/100 g
Verification unit [e]	50 g
Tare range	-300 kg
Stabilization time	2 s
Adjustment	external

Metrological parameters	
OIML Class	III
Physical parameters	
Leveling system	manual
Display	10" graphic colour touchscreen
Weighing pan dimensions	400×500 mm
Packaging dimensions	720×620×210 mm
Net weight	12.1 kg
Gross weight	14.1 kg
Cable length	2.5 m
Multiple range	YES
Construction	
Protection class	IP 43
Housing	steel + ABS
Communication interface	
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	12÷15V DC
Power consumption	1A
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Storage temperature	-25 ÷ +70 °C
Features of use	
Max number of platforms	max.2

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



Accessories

MediaBox
 Mild steel powder coated weighing platforms
 RFID Tags
 Power Adapters
 Additional Weighing platforms Module
 Mild steel powder coated weighing platforms
 Additional modules
 Platforms in plastic casing

Protective cover for balances
 Barcode scanners
 Label Printers
 RS 232, RS 485 cables
 Stands, wall mounting kits and mounting brackets
 Fingerprint Reader
 RS 232 – USB Converter
 Receipt Printer

Software

• E2R Weighing [WX-010-0099]

• E2R Weighing Records [WX-010-0038]

- RAD Key [WX-010-0005]
- RADWAG Remote Desktop [WX-010-0107]

- Label Editor R02 [WX-010-0094]
- Scale Editor 2.1 [WX-010-0173]

Device dimensions

