



More information on the website  
[radwag.com/en/info,w1,CM9](http://radwag.com/en/info,w1,CM9)

# PS 210.R2.H Precision Balance



The drawings, photos and graphics used are for illustrative purposes only.

## Functions

-  Autotest
-  Dosing
-  Percent Weighing
-  Totalizing
-  Parts counting
-  Peak hold
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  Under-pan weighing
-  GLP Procedures
-  Animal weighing
-  Density determination

## Datasheet

| Metrological parameters |          |
|-------------------------|----------|
| Maximum capacity [Max]  | 210 g    |
| Minimum load            | 20 mg    |
| Readability [d]         | 0.001 g  |
| Tare range              | -210 g   |
| Repeatability (Max)     | 0.001 g  |
| Repeatability (5% Max)  | 0.0005 g |

| Metrological parameters       |   |
|-------------------------------|---|
| Linearity                     | ±0.002 g  |
| Stabilization time            | 2 s   |
| Adjustment                    | internal (automatic)  |
| Sensitivity temperature drift | $2 \times 10^{-6} / ^\circ\text{C} \times \text{Rt}$                              |
| Physical parameters           |   |
| Leveling system               | manual  |
| Display                       | LCD (backlit)   |
| Weighing pan dimensions       | ∅100 mm   |
| Packaging dimensions          | 475×380×345 mm  |
| Net weight                    | 4.2 kg  |
| Gross weight                  | 6.2 kg  |
| Construction                  |   |
| Protection class              | IP 54   |
| Communication interface       |   |
| Communication interface       | 2×RS232 <sup>1</sup> , USB-A, USB-B, Wi-Fi (option)                               |
| Electrical parameters         |   |
| Power supply                  | Adapter: 100 – 240V AC 50/60Hz 0.6A; 12V DC 1.2A<br>Balance: 12 – 15V DC 0.4A max |
| Power consumption             | 4 W   |
| Environmental conditions      |   |
| Operating temperature         | +10 – +40 °C  |
| Relative humidity             | 40% – 80%   |

**Repeatability** is expressed as a standard deviation from 10 weighing cycles.

**Stabilization time** depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

<sup>1</sup> Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



## Accessories

Antivibration Tables  
Power Adapters  
Cigarette lighter receptacle power supply cables  
USB cable (scale - printer)  
Barcode scanners  
RS 232, RS 485 cables

Displays  
Receipt Printer  
RS 232, RS 485 cables  
Protective cover for balances  
Under-pan weighing  
RS 232 cables (scale - printer)

## Software

- RAD Key [WX-010-0005]
- Alibi Reader [WX-010-0114]
- RADWAG Development Studio [WX-010-0104]
- R-Panel [WX-010-0187]
- R-Lab [WX-010-0080]

## Device dimensions



PS R2.H, d = 1 mg



PS R2.M.H, d = 10 mg