



More information on the website
radwag.com/tr/info,w1,DIG

HX5.EX-1.4.6000.C10 4 Yk Hcreli Platform Terazi



The drawings, photos and graphics used are for illustrative purposes only.

Fonksiyonlar



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit
measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

Teknik Veriler

Metrolojik parametreler	
Maksimum yk [Max]	6000 kg
Minimum yk [Min]	40 kg
Okuma up tođruluđu [d]	2000 g
Dara aralıđı	-6000 kg
Fiziksel parametreler	
Display	5" graphic colour
Tartım kefi boyutları	1500x2000 mm

Fiziksel parametreler	
Net ağırlık	237,8 kg
Brüt ağırlık	238 kg
Kablo uzunluğu	3 m
Sertifikasyon ATEX	II 2G Ex ib IIB T4 Gb
Sertifikasyon IECEx	Ex ib IIB T4 Gb
İndikatör	PUE HX5.EX-1
Konstrüksiyon	
IP Sınıfı	IP 65 construction, IP 66/68 indicator
Konstrüksiyon	mild steel St3S
Haberleşme arayüzler	
Haberleşme arayüzü	2×RS232, RS485
Elektrik parametreleri	
Güç kaynağı	100 – 240 V AC 50/60 Hz
Maksimum güç tüketimi	15 W
Çevresel koşullar	
Çalıştırma sıcaklığı	-10 ÷ +40 °C
Atmosferik nem	10% ÷ 85% RH no condensation



Extra payment for verification



Aksesuarlar

Haberleşme modülü
Terazi için tasarlanmış kendinden korumalı güç kaynağı

Fiş yazıcı

Yazılım

- E2R Tartım [WX-010-0099]
- RAD Key [WX-010-0005]
- Alibi Okuyucu PC Yazılımı [WX-010-0114]
- Terazi Editörü - EWAG 2.1 [WX-010-0173]

- E2R Tartı Kayıtları [WX-010-0038]
- Etiket Editörü R02 [WX-010-0094]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]