



C315.10/20.D-1 Baby Scale

WM-001-1011

More information on the website
radwag.com/en/info,w1,EPZ



The drawings, photos and graphics used are for illustrative purposes only.

Functions



Internal battery



Peak hold



GLP Procedures



ALIBI Memory

Datasheet

Metrological parameters	
Maximum capacity [Max]	10 / 20 kg
Readability [d]	5 / 10 g
Tare range	-20 kg
OIML Class	III
Physical parameters	
Display	LCD (backlit)
Packaging dimensions	600×520×180 mm
Net weight	3.5 kg
Communication interface	
Communication interface	RS232

Electrical parameters

Power supply	100 – 240 V AC 50/60 Hz and battery
Power consumption max.	5 W
Operation time on batteries	up to 8 h

Environmental conditions

Operating temperature	0 – +40 °C
Relative humidity	10% – 85% RH no condensation

According to MDR regulations, this scale is not a medical device.



Additional fee for verification

Accessories (Additional Fee)

Power Adapters
RS 232 cables (scale - printer)
Cigarette lighter receptacle power supply cables
Displays
Displays
RS 232, RS 485 cables

RS 232 – Ethernet Converter
AP2-1 Current Loop Unit
RS 232, RS 485 cables
RS 232 – USB Converter
RS 232 – RS 485 Converter
Receipt Printer

Software (Additional Fee)

• RAD Key [WX-010-0005]
• R-Lab [WX-010-0080]

• R-Panel [WX-010-0187]
• Scale Editor 2.1 [WX-010-0173]

Device dimensions

