



# CY10.60.C2.K.M3 Multifunctional Scale

More information on the website  
[radwag.com/en/info,w1,G86](http://radwag.com/en/info,w1,G86)



The drawings, photos and graphics used are for illustrative purposes only.

## Functions

-  Autotest
-  Dosing
-  Percent Weighing
-  Parts counting
-  Peak hold
-  Formulation
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  IR sensors
-  GLP Procedures
-  Animal weighing
-  Pipettes Calibration
-  Air density correction
-  Density determination
-  Differential weighing
-  Ambient conditions monitoring
-  Statistical Quality Control
-  Packaged Goods Control
-  ALIBI Memory
-  Wi-Fi

## Datasheet

### Metrological parameters

|                        |       |
|------------------------|-------|
| Maximum capacity [Max] | 60 kg |
| Minimum load           | 400 g |

| <b>Metrological parameters</b>         |  |
|--|--|
| Readability [d]                        | 20 g   |
| Verification unit [e]                  | 20 g   |
| Tare range                             | -60 kg   |
| Max readability for non-verified scale | 2 g  |
| Stabilization time                     | 2 s  |
| Adjustment                             | external                                       |
| OIML Class                             | III  |
| <b>Physical parameters</b>             |  |
| Leveling system                        | manual   |
| Display                                | 10" graphic colour touchscreen                 |
| Weighing pan dimensions                | 400×500 mm                                     |
| Packaging dimensions                   | 720×620×210 mm                                 |
| Net weight                             | 12.1 kg  |
| Gross weight                           | 14.1 kg  |
| Cable length                           | 2.5 m  |
| Multiple range                         | YES  |
| <b>Construction</b>                    |  |
| Protection class                       | IP 43  |
| Housing                                | steel + ABS                                    |
| <b>Communication interface</b>         |  |
| Communication interface                | 2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot |
| <b>Electrical parameters</b>           |  |
| Power supply                           | 12÷15V DC                                      |
| Power consumption                      | 1A   |
| <b>Environmental conditions</b>        |  |
| Operating temperature                  | -10 ÷ +40 °C                                   |
| Storage temperature                    | -25 ÷ +70 °C                                   |
| <b>Features of use</b>                 |  |
| Max number of platforms                | max.2  |

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



## Accessories

MediaBox  
Mild steel powder coated weighing platforms  
RFID Tags  
Power Adapters  
Additional Weighing platforms Module

Protective cover for balances  
Barcode scanners  
Label Printers  
RS 232, RS 485 cables  
Fingerprint Reader

Mild steel powder coated weighing platforms  
Additional modules  
Platforms in plastic casing

RS 232 – USB Converter  
Receipt Printer

## Software

- E2R Weighing [WX-010-0099]
- RAD Key [WX-010-0005]
- RADWAG Remote Desktop [WX-010-0107]
- E2R Weighing Records [WX-010-0038]
- Label Editor R02 [WX-010-0094]
- Scale Editor 2.1 [WX-010-0173]

## Device dimensions

