



More information on the website
radwag.com/en/info,w1,GRZ

High Resolution Platforms PL.16.HRP



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Metrological parameters	
Maximum capacity [Max]	16 kg
Preload range	4 kg
Readability [d]	0.1 g
Tare range	-16 kg
Repeatability	0.1 g
Linearity	±0.1 g
Adjustment	internal (automatic)
Construction	
Protection class	IP 67
Construction	aluminum
Weighing pan material	Stainless steel AISI304
Communication interface	
Communication interface	RS232, RS485, Ethernet

Electrical parameters

Power supply 100 – 240 V AC 50/60 Hz

Environmental conditions

Operating temperature +10 ÷ +40 °C

Relative humidity 15% – 80%

Physical parameters

Weighing pan dimensions 360×280 mm

Packaging dimensions 475×560×370 mm

Net weight 14.6 kg

Gross weight 18.6 kg



Accessories

RS 232 cables (scale - Ethernet)

Antivibration Tables

PUE 7.1 Weighing Terminal

RS 232, RS 485 cables

IN/OUT Cables

Powerbanks

PUE HY10 Weighing Terminal

Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX

Weighing Terminal

CY10 Precision Balance

RS 232 – USB Converter

Software

• MWMH Manager [WX-010-0103]

• RADWAG Development Studio [WX-010-0104]

• RAD Key [WX-010-0005]

Device dimensions



PL.16 - 32.HRP



PL.62-2000.HRP

Scale type	A1	A2	H
PL.(16-32).HRP	360	280	180±5
PL.(62-150).HRP	500	400	180±5
PL.150.2.HRP	500	500	180±5
PL.(150.1-300).HRP	800	600	180±5
PL.(300.1-1100).HRP	1000	800	180±5
PL.(2000).HRP	1250	1000	180±5

Dimensions in mm