

RMC 2.5Y.F Robotic Weighing System





The drawings, photos and graphics used are for illustrative purposes only.

Functions

Q	Autotest		Dosing	%	Percent Weighing	***	Parts counting
	Formulation	/	Newton unit measurement	<u>l</u>	Statistics	- <u>0K</u> +	Checkweighing
4	IR sensors	GLP	GLP Procedures		Animal weighing	≋	Air density correction
	Differential weighing		Ambient conditions monitoring	G	Replaceable unit	SQC	Statistical Quality Control

Wi-Fi

Datasheet

ALIBI Memory

Metrological parameters				
Maximum capacity [Max]	2.1 g			
Readability [d]	1 µg			
Verification unit [e]	1 mg			
Tare range	-2.1 g			

Metrological parameters					
Repeatability (Max)	1 - 2 µg				
Repeatability (5% Max)	0.5 µg				
Linearity	≤ 1.5 µg				
Stabilization time	10 - 20 s				
Adjustment	internal				
OIML Class	T.				
Physical parameters					
Display	10" graphic colour touchscreen				
Device dimensions	2108×1067×1595 mm				
Net weight	400 kg				
Gross weight	500 kg				
Features of use					
Touch-free operation	2 IR Sensors				
Communication interface					
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot				
Electrical parameters					
Power supply	110 - 240 V AC 50/60 Hz				
Environmental conditions					
Operating temperature	+10 ÷ +40 °C				
Storage temperature	-20 ÷ +50 °C				
Operating temperature change rate	±0.3°C/1h (±1°C/8h)				
Relative humidity	30% ÷ 70%				
Relative humidity change rate	±1%/h (±4%/8h)				
Construction					
Keypad	8 przycisków				
D . 1.000 1	40				

Repeatability is expressed as a standard deviation from 10 weighing cycles.

Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile.

^{*} Wi-Fi® is a registered trademark of Wi-Fi® Alliance.





Extra payment for verification (




Accessories


RFID Tags Additional modules Protective cover for balances RS 232, RS 485 cables Receipt Printer Fingerprint Reader

Software


• Scale Editor 2.1 [WX-010-0173]


Device dimensions





RMC 2.4Y.F





RMC 2.4Y.FC