



More information on the website  
[radwag.com/en/info,w1,l48](http://radwag.com/en/info,w1,l48)

# THB P PRO Sensor



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

Temperature readability [d]	0.001 °C
Temperature measurement accuracy	± 0.1 °C (+5 °C – +45 °C) °C
Measured pressure range	300 – 1250 hPa
Pressure readability [d]	0.001 hPa
Pressure measurement accuracy	±0.5 hPa
Measured humidity range	0 – 100 %
Operating temperature	+5 – +45 °C
Humidity readability [d]	0.01 %
Humidity measurement accuracy	± 1 % RH (20 % – 70 %, +20 °C – +50 °C)
Communication interface	USB 2.0
Vibrations detection	YES
Air density determination	YES
Measured temperature range	0 – +50 °C
<b>Physical parameters</b>	
Net weight	260 g
Gross weight	400 g



## Compatible with

XA 5Y.M.A.P Microbalance for pipettes calibration  
MYA 5Y.P Microbalance for pipettes calibration  
MYA 5Y.F Microbalance for Filters  
XA 5Y.M.A Microbalance  
Automatic Balances for. Pipettes Calibration  
XA 5Y.A Analytical Balance  
WAY 5Y.KO Manual Mass Comparator  
Robotic Mass Comparators  
UYA 5Y Ultra-Microbalance  
AS 5Y Analytical Balance  
AK-4 Automatic Mass Comparator  
PS 5Y Balances for PGC  
AKM-2 Automatic Mass Comparator  
XA 5Y.F Analytical Balance for Filters  
UMA Automatic Mass Comparator  
APP 5Y.KO Manual Mass Comparator

Density Measurement  
MYA 5Y Microbalance  
XA 5Y Analytical Balance  
5Y.PM.KB Manual Mass Comparator  
HRP 5Y.KO Mass Comparator  
PS 5Y Precision Balance  
Automatic Vacuum Mass Comparators  
XA 5Y.KO Manual Mass Comparator  
HRP 5Y.KB Mass Comparator  
THBR 2.0 System - Ambient Conditions Monitoring  
XA 5Y.M Microbalance  
UYA 5Y.KO Manual Mass Comparator  
UYA 5Y.F Ultra-Microbalance for Filters  
Nano-Comparator NANO.AK-4.500.5Y  
XA 5Y.M.A.S Microbalance for stents weighing

## Software

• THB-R [WX-010-0122]