



More information on the website  
[radwag.com/us/info,w1,KLX](http://radwag.com/us/info,w1,KLX)

# HX5.EX-1.4.6000.C11 4 Load Cell Platform Scale



The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

## Datasheet

|                            |                   |
|----------------------------|-------------------|
| Maximum capacity [Max]     | 6000 kg           |
| Minimum load               | 40 kg             |
| Readability [d]            | 2000 g            |
| Tare range                 | -6000 kg          |
| <b>Physical parameters</b> |                   |
| Display                    | 5" graphic colour |
| Cable length               | 3 m               |

| Physical parameters     |                                       |
|-------------------------|---------------------------------------|
| Weighing pan dimensions | 2000×2000 mm                          |
| Net weight              | 357,8 kg                              |
| Gross weight            | 358 kg                                |
| Construction            |                                       |
| Protection class        | IP 65 construction, IP 66/68 terminal |
| Construction            | mild steel St3S                       |
| ATEX Certification      | II 2G Ex ib IIB T4 Gb                 |
| IECEX Certification     | Ex ib IIB T4 Gb                       |
| Indicator               | PUE HX5.EX-1                          |
| Communication interface |                                       |
| Communication interface | 2×RS232, RS485                        |
| Power supply            |                                       |
| Power supply            | 100 – 240 V AC 50/60 Hz               |
| Power consumption max.  | 15 W                                  |
| Operating temperature   |                                       |
| Operating temperature   | -10 – +40 °C                          |
| Relative humidity       |                                       |
| Relative humidity       | 10% – 85% RH no condensation          |



Extra payment for verification



## Accessories

Communication modules  
 Ex-Scale-Intended Intrinsically Safe Power Supply for PUE HX5.EX  
 Weighing Terminal

Receipt Printer

## Software

- E2R Weighing [WX-010-0099]
- RAD Key [WX-010-0005]
- Alibi Reader PC Software [WX-010-0114]
- RADWAG Development Studio [WX-010-0104]

- E2R Weighing Records [WX-010-0038]
- Label Editor R02 [WX-010-0094]
- Scale Editor - EWAG 2.1 [WX-010-0173]