



More information on the website
radwag.com/en/info,w1,MWB

Multi-Track DWM H2 Checkweigher

WK-105-00_



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

| Metrological parameters | |
|--|---|
| Maximum capacity [Max] | 1500 – 7500 g |
| Minimum load | 4 – 20 g |
| Readability [d] | 0.2 – 1 g |
| Verification unit [e] | 0.2 – 1 g |
| Tare range | -1500 – -7500 g |
| Max readability for non-verified scale | 0.2 – 1 g |
| Expanded reading unit | 0.01 – 0.5 g |
| OIML Class | XIII (1), Y (a) |
| Construction | |
| Protection class | IP 55, IP 65 |
| Keypad | touch screen |
| Construction | mild steel / Stainless steel |
| Communication interface | |
| Communication interface | Ethernet, USB, RS232, I / O, Modbus, ProfiNet (option), ProfiBus (option) |

Electrical parameters

Power supply 100 – 240 V AC 50/60 Hz

Environmental conditions

Operating temperature +5 – +40 °C

Features of use

Conveyor velocity 1.6 m/s



Accessories (Additional Fee)

RS 232 cables (scale - ZEBRA printer)

RS 232, RS 485 cables

Tunnel Detectors

Keypad, external switches

USB adapter

Receipt Printer

USB cable (scale - printer)

Software (Additional Fee)

• Label Editor R02 [WX-010-0094]

• E2R Checkweigher [WX-010-0055]