



More information on the website
radwag.com/us/info,w1,P46

DWM HY10 Basic Checkweigher



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Maximum capacity [Max]	1500 – 6000 g
Readability [d]	0,5 – 2 g
Physical parameters	
Display	10,1" graphic colour touchscreen
Operating pressure	6 Bar
Construction	
Protection class	IP 55
Material	Stainless steel, aluminium anodowane
Communication interface	RS232, Ethernet, RS485
Optional interfaces	Profibus, Profinet, Ethernet IP, Modbus
Power supply	110 – 230 V AC 50 – 60 Hz
Power consumption max.	0,6 kVA

Operating temperature +10 – +40 °C

Features of use

Capacity max 150 pcs/min

Conveyor velocity max 1 m/s



Device dimensions

Entry conveyor [L1]				
Width \ Length	300	350	400	450
	150	x	x	x
200	x	x	x	x
250	x	x	x	x
300*		x	x	x

Discriminating conveyor [L3]			
Width \ Length	500*	600	650*
	150	x	x
200	x	x	x
250	x	x	X
300	x	x	x

Weighing Conveyor [L2]				
Width \ Length	300	350	400	450
	150	x	x	x
200	x	x	x	x
250	x	x	x	x
300*		x	x	x

Capacities depending on the size of the conveyor L2				
Width \ Length	300	350	400	450
	150	1500g	1500g	6000g
200	3000g	3000g	6000g	6000g
250	3000g	3000g	6000g	6000g
300*		3000g	6000g	6000g

*option

Working height [H]

I	Height 700 mm
II	Height 900 mm

Adjustment range

+/- 100 mm

+/- 100 mm

