



HRP 2000.1.5Y.KO Mass Comparator

More information on the website
radwag.com/us/info,w1,PZI



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

E1	-
E2	-
F1	-
F2	-
M1	500 kg ÷ 2000 kg
M2	500 kg ÷ 2000 kg
Maximum capacity [Max]	2100 kg
Readability [d]	5 g
Standard repeatability [5% Max]	5 g
Standard repeatability [Max]	10 g
Permissible repeatability	15 g
Eccentricity (tested load)	0,5d / 1 mm
Electric compensation range	0 ÷ 2100 kg
Stabilization time	10 s
Adjustment	internal (automatic)

Physical parameters	
Display	10" graphic colour touchscreen
Weighing pan dimensions	1250×1000 mm
Self-centering weighing pan dimensions	920×920 (extra charge) mm
Weighing unit dimensions with self-centering weighing pan	1250×1000×400 mm
Controlling device dimensions	249×170×72 mm
Comparator packaging dimensions without self-centering weighing pan	1500×1250×615 mm
Comparator packaging dimensions with self-centering weighing pan	1500×1200×713 mm
Net weight/gross weight (comparator)	300 / 400 kg
Net weight/Gross weight with self-centering weighing pan	530 / 665 kg
Recommended load speed	0,3 m/min
Weighing unit dimensions without self-centering weighing pan	1250×1000×235 mm
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Operating temperature	+15 ÷ +30 °C
Operating temperature change rate	±2°C/12h
Relative humidity	40% ÷ 60%
Relative humidity change rate	±10%/4h

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

RFID Tags
 Additional modules
 Protective cover for balances
 Barcode scanners

THBR 2.0 System - Ambient Conditions Monitoring
 RS 232, RS 485 cables
 Receipt Printer
 Fingerprint Reader

Software

- RAD Key [WX-010-0005]
- RMCS System Network Management of Calibration Process [WX-010-0048]

- RMCS Lite [WX-010-0164]

Device dimensions



Type	A1	A2	H
HRP 200.5Y.KO	809	600	162
HRP 500.5Y.KO	809	600	162
HRP 1000.5Y.KO	1011	800	182
HRP 1500.5Y.KO	1250	1000	235
HRP 2000.5Y.KO	1250	1000	235

Dimensions in mm