



More information on the website  
[radwag.com/en/info,w1,QBE](http://radwag.com/en/info,w1,QBE)

# PLC/300/C2 Platform



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

| Metrological parameters |                         |
|-------------------------|-------------------------|
| Maximum capacity [Max]  | 300 kg                  |
| Readability [d]         | 100 g                   |
| Construction            |                         |
| Protection class        | IP 65                   |
| Construction            | mild steel St3S         |
| Weighing pan material   | Stainless steel AISI304 |
| Physical parameters     |                         |
| Weighing pan dimensions | 400×500 mm              |
| Packaging dimensions    | 720×620×210 mm          |

**Readability accuracy** – expected value, dependent on the parameters of the measuring transmitter used.





# Accessories



CY10 Scales for PGC  
 PUE CY10 Weighing Terminal  
 CY10 Multifunctional Scale  
 PUE 5 Weighing Terminal  
 CY10 Precision Balance  
 PUE C32 Weighing Terminal

PUE 7.1 Weighing Terminal  
 PUE HX7 Weighing Terminal  
 PUE C315 Weighing Terminal  
 PUE HY10 Weighing Terminal  
 PUE H315 Weighing Terminal


## Device dimensions





PL/D2



PLC/F1



PLC/C2  
PLC/C3



PL/H  
PL/HR

| Platform type       | A1  | A2  | H     |
|---------------------|-----|-----|-------|
| PL/D2               | 238 | 216 | 82±3  |
| PLC/F1              | 300 | 300 | 70±3  |
| PLC/C2              | 402 | 502 | 103±3 |
| PLC/C3              | 701 | 501 | 130±5 |
| PL/H1 / PL/HR1      | 150 | 200 | 85±3  |
| PL/H2 / PL/HR2      | 250 | 300 | 103±3 |
| PL/H3 / PL/HR/3     | 410 | 410 | 98±3  |
| PL/H3/5 / PL/HR/3/5 | 400 | 600 | 155±3 |
| PL/H4 / PL/HR/4     | 500 | 500 | 155±3 |
| PL/H5 / PL/HR/5     | 600 | 600 | 155±3 |
| PL/H6               | 800 | 800 | 135±3 |

dimensions in mm