



More information on the website  
[radwag.com/en/info,w1,QL2](http://radwag.com/en/info,w1,QL2)

# C315.4.60.C6 Platform Scale



The drawings, photos and graphics used are for illustrative purposes only.

## Functions

 Plus/Minus Control

 Percent Weighing

 Totalizing

 Parts counting

 Internal battery

 Peak hold

 Newton unit measurement

 GLP Procedures

 Animal weighing

 ALIBI Memory

## Datasheet

| Metrological parameters                |         |
|--|---------|
| Maximum capacity [Max]                 | 60 kg   |
| Minimum load                           | 0.4 kg  |
| Readability [d]                        | 0.02 kg |
| Tare range                             | -60 kg  |
| Max readability for non-verified scale | 20 g    |
| OIML Class                             | III     |

| Physical parameters         |                                     |
|-----------------------------|-------------------------------------|
| Display                     | LCD (backlit)                       |
| Cable length                | 3 m                                 |
| Weighing pan dimensions     | 800×800 mm                          |
| Weighing platform height    | 116 ± 6 mm                          |
| Packaging dimensions        | 900×900×500 mm                      |
| Scale mass with indicator   | 55 kg                               |
| Construction                |                                     |
| Protection class            | IP 65 construction, IP 43 terminal  |
| Communication interface     |                                     |
| Communication interface     | RS232                               |
| Optional interfaces         | RS232                               |
| Electrical parameters       |                                     |
| Power supply                | 100 – 240 V AC 50/60 Hz and battery |
| Power consumption max.      | 5 W                                 |
| Operation time on batteries | max 8h                              |
| Environmental conditions    |                                     |
| Operating temperature       | -10 – +40 °C                        |
| Relative humidity           | 10% – 85% RH no condensation        |



Extra payment for verification



## Accessories

Power Adapters  
 RS 232 cables (scale - printer)  
 Stands, wall mounting kits and mounting brackets  
 Cigarette lighter receptacle power supply cables  
 Displays  
 Frame for embedded scales  
 Ramps  
 Displays

RS 232, RS 485 cables  
 RS 232 – Ethernet Converter  
 AP2-1 Current Loop Unit  
 RS 232, RS 485 cables  
 RS 232 – USB Converter  
 RS 232 cables (scale - printer)  
 RS 232 – RS 485 Converter  
 Receipt Printer

## Software

- RAD Key [WX-010-0005]
- R-Lab [WX-010-0080]

- R-Panel [WX-010-0187]
- Scale Editor 2.1 [WX-010-0173]

## Device dimensions



|         | A    | B    | H       |
|---------|------|------|---------|
| C6      | 800  | 800  | 120 ±10 |
| C7      | 1000 | 1000 | 120 ±10 |
| C8      | 1200 | 1200 | 120 ±10 |
| C8/9    | 1200 | 1500 | 120 ±10 |
| C9      | 1500 | 1500 | 120 ±10 |
| 6000.C9 | 1500 | 1500 | 160 ±10 |