



More information on the website
radwag.com/en/info,w1,TQG

HX5.EX-1.15.H1 One Load Cell Platform Scale



The drawings, photos and graphics used are for illustrative purposes only.

Functions



Labelling



Plus/Minus Control



Percent Weighing



Parts counting



Newton unit measurement



Statistics



GLP Procedures



Replaceable unit



ALIBI Memory

Datasheet

Metrological parameters	
Maximum capacity [Max]	15 kg
Minimum load	100 g
Readability [d]	5 g
Tare range	-15 kg
OIML Class	III
Physical parameters	
Display	5" graphic colour

Physical parameters	
Protection class	IP 68 construction, IP 66/68 indicator
Weighing pan dimensions	150×200 mm
Packaging dimensions	290×270×240 mm
Net weight	11,5 kg
Gross weight	12,5 kg
ATEX Certification	II 2G Ex ib IIB T4 Gb
IECEX Certification	Ex ib IIB T4 Gb
Indicator	PUE HX5.EX-1
Weighing pan material	stainless steel AISI304
Communication interface	
Communication interface	2×RS232, RS485
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz
Power consumption max.	15 W
Environmental conditions	
Operating temperature	-10 ÷ +40 °C
Relative humidity	10% ÷ 85% RH no condensation
Construction	
Construction	Stal stainless steel AISI304



Accessories

Communication modules
Power Adapters
Communication Modules

Stands, wall mounting kits and mounting brackets
Receipt Printer

Software

RAD-KEY
R-LAB
E2R System

LabVIEW Driver
RADWAG Development Studio
R.Barcode