



More information on the website  
[radwag.com/en/info,w1,YNJ](http://radwag.com/en/info,w1,YNJ)

# THB W Liquid Temperature Sensor

WX-016-0162



The drawings, photos and graphics used are for illustrative purposes only.

## Datasheet

| Metrological parameters          |             |
|----------------------------------|-------------|
| Temperature readability [d]      | 0.01 °C     |
| Temperature measurement accuracy | ±0.1        |
| Measured temperature range       | +5 – +45 °C |
| Temperature readability          | 0.01 °C     |
| Communication interface          | USB 2.0     |
| Physical parameters              |             |
| Sensor unit dimensions           | ø 8×156 mm  |



## Compatible with (Additional Fee)

XA 5Y.M.A.P Microbalance for pipettes calibration  
 MYA 5Y.P Microbalance for pipettes calibration  
 MYA 5Y.F Microbalance for Filters  
 AS X7 Analytical Balance

Density Measurement  
 MYA 5Y Microbalance  
 XA 5Y Analytical Balance  
 Manual susceptometers - Magnetization

PS X2 Precision Balance  
AS X2 PLUS Analytical Balances  
XA 5Y.M.A Microbalance  
PS X7 Precision Balance  
XA 5Y.A Analytical Balance  
WAY 5Y.KO Manual Mass Comparator  
AS 5Y Analytical Balance  
AK-4 Automatic Mass Comparator  
PS 5Y Balances for PGC  
AKM-2 Automatic Mass Comparator  
XA 5Y.F Analytical Balance for Filters  
UMA Automatic Mass Comparator  
APP 5Y.KO Manual Mass Comparator  
Robotic Mass Comparators

5Y.PM.KB Manual Mass Comparator  
HRP 5Y.KO Mass Comparator  
PS 5Y Precision Balance  
Workstation for Pipettes Calibration  
Automatic Vacuum Mass Comparators  
Automatic susceptometers - Magnetization  
XA 5Y.KO Manual Mass Comparator  
HRP 5Y.KB Mass Comparator  
THBR 2.0 System - Ambient Conditions Monitoring  
XA 5Y.M Microbalance  
UYA 5Y.KO Manual Mass Comparator  
Nano-Comparator NANO.AK-4.500.5Y  
XA 5Y.M.A.S Microbalance for stents weighing

## Software (Additional Fee)

• THB-R [WX-010-0122]