



More information on the website
radwag.com/us/info,w1,Z8Y

THB W PRO Sensor



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Temperature measurement accuracy	$\pm 0,1 \text{ }^\circ\text{C}$ (+5 $^\circ\text{C}$ – +45 $^\circ\text{C}$)
Measured temperature range	0 – +50 $^\circ\text{C}$
Temperature readability	0,01 $^\circ\text{C}$
Communication interface	USB 2.0
Physical parameters	
Sensor unit dimensions	$\varnothing 8 \times 156 \text{ mm}$



Compatible with (Additional Fee)

XA 5Y.M.A.P Microbalance for pipettes calibration
 MYA 5Y.P Microbalance for pipettes calibration
 MYA 5Y.F Microbalance for Filters
 AS X7 Analytical Balance
 PS X2 Precision Balance
 AS X2 PLUS Analytical Balances

APP 5Y.KO Manual Mass Comparator
 Robotic Mass Comparators
 Density measurement
 MYA 5Y Microbalance
 XA 5Y Analytical Balance
 5Y.PM.KB Manual Mass Comparator

XA 5Y.M.A Microbalance
Susceptometer - Magnetization
PS X7 Precision Balance
XA 5Y.A Analytical Balance
WAY 5Y.KO Manual Mass Comparator
AS 5Y Analytical Balance
AK-4 Automatic Mass Comparator
PS 5Y Balances for PGC
AKM-2 Automatic Mass Comparator
Analytical Balance for Filters XA 5Y.F
UMA Automatic Mass Comparator

HRP 5Y.KO Mass Comparator
PS 5Y Precision Balance
Workstation for pipettes calibration
Automatic Vacuum Mass Comparators
XA 5Y.KO Manual Mass Comparator
HRP 5Y.KB Mass Comparator
THBR 2.0 System - Ambient Conditions Monitoring
XA 5Y.M Microbalance
UYA 5Y.KO Manual Mass Comparator
Nano-Comparator NANO.AK-4.500.5Y
XA 5Y.M.A.S Microbalance for stents weighing

Software (Additional Fee)

• THB-R [WX-010-0122]