



CY10.30/60.C2.K Precision Balance, CY10.60/120.C2.K Precision Balance, CY10.120.C2.K Precision Balance, CY10.60.C2.K.M2 Precision Balance

More information on the website
radwag.com/en/info,w1,8TV



CY10.30/60.C2.K Precision Balance
 CY10.60/120.C2.K Precision Balance
 CY10.120.C2.K Precision Balance
 CY10.60.C2.K.M2 Precision Balance

The drawings, photos and graphics used are for illustrative purposes only.

Functions



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit measurement



Statistics



Checkweighing



IR sensors



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Differential weighing



Ambient conditions monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

Datasheet

	CY10.30/60.C2.K Precision Balance	CY10.60/120.C2.K Precision Balance	CY10.60.C2.K.M2 Precision Balance
Metrological parameters			
Maximum capacity [Max]	30/60 kg	60/120 kg	60 kg
Minimum load	-	-	50 g
Readability [d]	0,5/1 g	1/2 g	1 g
Verification unit [e]	-	-	10 g
Tare range	-60 kg	-120 kg	-60 kg
Repeatability	1,5 g	2 g	1,5 g
Linearity	±3 g	±2 g	±3 g
Stabilization time	3 s	3 s	3 s
Adjustment	external	external	external
OIML Class	-	-	II
Physical parameters			
Leveling system	manualny	manualny	manualny
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Weighing pan dimensions	400×500 mm	400×500 mm	400×500 mm
Packaging dimensions	720×620×210 mm	720×620×210 mm	720×620×210 mm
Net weight	13,5 kg	13,5 kg	13,5 kg
Gross weight	16 kg	16 kg	16 kg
Construction			
Protection class	IP 43	IP 43	IP 43
Housing	steel + ABS	steel + ABS	steel + ABS
Communication interface			
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters			
Power supply	12÷15V DC	12÷15V DC	12÷15V DC
Power consumption	1A	1A	1A
Environmental conditions			
Operating temperature	+15 ÷ +30 °C	+15 ÷ +30 °C	+15 ÷ +30 °C
Storage temperature	-25 ÷ +70 °C	-25 ÷ +70 °C	-25 ÷ +70 °C
Relative humidity	10% ÷ 80% RH no condensation	10% ÷ 80% RH no condensation	10% ÷ 80% RH no condensation

Datasheet

	CY10.120.C2.K Precision Balance
Metrological parameters	
Maximum capacity [Max]	120 kg
Minimum load	-
Readability [d]	2 g
Verification unit [e]	-
Tare range	-120 kg
Repeatability	2 g
Linearity	±2 g
Stabilization time	3 s
Adjustment	external
OIML Class	-
Physical parameters	
Leveling system	manualny
Display	10" graphic colour touchscreen
Weighing pan dimensions	400×500 mm
Packaging dimensions	720×620×210 mm
Net weight	13,5 kg
Gross weight	16 kg
Construction	
Protection class	IP 43
Housing	steel + ABS
Communication interface	
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	12÷15V DC
Power consumption	1A
Environmental conditions	
Operating temperature	+15 ÷ +30 °C
Storage temperature	-25 ÷ +70 °C
Relative humidity	10% ÷ 80% RH no condensation

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

MediaBox
Mild steel powder coated weighing platforms
HRP Platforms High Capacity
RFID Tags
Power Adapters
Additional Weighing platforms Module
Mild steel powder coated weighing platforms
Additional modules
Platforms in plastic casing

Professional Weighing Tables
Protective cover for balances
Barcode scanners
RS 232, RS 485 cables
Label Printers
RS 232, RS 485 cables
Receipt Printer
Fingerprint Reader
RS 232 – USB Converter

Software

E2R System
Label Editor R02
Scales Editor 2.1

RAD-KEY
RADWAG Remote Desktop

Device dimensions

CY10.30/60.C2.K Precision Balance, CY10.60/120.C2.K Precision Balance, CY10.120.C2.K Precision Balance, CY10.60.C2.K.M2 Precision Balance

