




More information on the website
radwag.com/en/info,w1,JCI


C32.150.C3.M Multifunctional Scale, C32.6.F1.M Multifunctional Scale, C32.15.C2.M Multifunctional Scale, C32.60.C2.M Multifunctional Scale, C32.30.F1.M Multifunctional Scale, C32.15.F1.M Multifunctional Scale, C32.15.C3.M Multifunctional Scale, C32.1,5.F1.M Multifunctional Scale, C32.60.C3.M Multifunctional Scale, C32.3.F1.M Multifunctional Scale, C32.150.C2.M Multifunctional Scale, C32.300.C2.M Multifunctional Scale, C32.300.C3.M Multifunctional Scale, C32.30.C3.M Multifunctional Scale




C32.150.C3.M Multifunctional Scale
C32.60.C3.M Multifunctional Scale
C32.30.C3.M Multifunctional Scale



C32.6.F1.M Multifunctional Scale
C32.15.F1.M Multifunctional Scale
C32.1,5.F1.M Multifunctional Scale
C32.3.F1.M Multifunctional Scale




C32.15.C2.M Multifunctional Scale




C32.60.C2.M Multifunctional Scale
C32.150.C2.M Multifunctional Scale




C32.30.F1.M Multifunctional Scale



C32.15.C3.M Multifunctional Scale



C32.300.C2.M Multifunctional Scale



C32.300.C3.M Multifunctional Scale

The drawings, photos and graphics used are for illustrative purposes only.

Functions



Labelling



Plus/Minus Control



Percent Weighing



Totalizing



Parts counting

Newton unit
measurement

Statistics



IR sensors



Under-pan weighing



GLP Procedures



Replaceable unit



ALIBI Memory

Datasheet

	C32.1.5.F1.M Multifunctional Scale	C32.3.F1.M Multifunctional Scale	C32.6.F1.M Multifunctional Scale
Metrological parameters			
Maximum capacity [Max]	1,5 kg	3 kg	6 kg
Minimum load	10 g	20 g	40 g
Readability [d]	0,5 g	1 g	2 g
Tare range	-1,5 kg	-3 kg	-6 kg
Max readability for non-verified scale	0,2 g	0,2 g	0,2 g
OIML Class	III	III	III
Physical parameters			
Display	5" graphic colour	5" graphic colour	5" graphic colour
Weighing pan dimensions	300×300 mm	300×300 mm	300×300 mm
Packaging dimensions	570×390×170 mm	570×390×170 mm	570×390×170 mm
Net weight	5,3 kg	5,3 kg	5,3 kg
Gross weight	6,6 kg	6,6 kg	6 kg
Construction			
Protection class	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator
Construction	mild steel St3S	mild steel St3S	mild steel St3S
Weighing pan material	Stainless steel AISI304	Stainless steel AISI304	Stainless steel AISI304
Communication interface			
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters			
Power supply	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz
Power consumption max.	10 W	10 W	10 W
Optional power supply	internal rechargeable battery	internal rechargeable battery	internal rechargeable battery
Operation time on batteries	operation time up to 5 h	operation time up to 5 h	operation time up to 5 h
Environmental conditions			
Operating temperature	-10 ÷ +40 °C	-10 ÷ +40 °C	-10 ÷ +40 °C

Datasheet

	C32.15.F1.M Multifunctional Scale	C32.15.C2.M Multifunctional Scale	C32.15.C3.M Multifunctional Scale
Metrological parameters			
Maximum capacity [Max]	15 kg	15 kg	15 kg
Minimum load	100 g	100 g	100 g
Readability [d]	5 g	5 g	5 g
Tare range	-15 kg	-15 kg	-15 kg
Max readability for non-verified scale	0,5 g	1 g	1 g
OIML Class	III	III	III
Physical parameters			
Display	5" graphic colour	5" graphic colour	5" graphic colour
Weighing pan dimensions	300×300 mm	500×400 mm	700×500 mm
Packaging dimensions	570×390×170 mm	720×620×210 mm	730×800×270 mm
Net weight	5,3 kg	12,8 kg	23,4 kg
Gross weight	6,6 kg	14,8 kg	27,2 kg
Construction			
Protection class	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator
Construction	mild steel St3S	mild steel St3S	mild steel St3S
Weighing pan material	Stainless steel AISI304	Stainless steel AISI304	Stainless steel AISI304
Communication interface			
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters			
Power supply	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz
Power consumption max.	10 W	10 W	10 W
Optional power supply	internal rechargeable battery	internal rechargeable battery	internal rechargeable battery
Operation time on batteries	operation time up to 5 h	operation time up to 5 h	operation time up to 5 h
Environmental conditions			
Operating temperature	-10 ÷ +40 °C	-10 ÷ +40 °C	-10 ÷ +40 °C

Datasheet

	C32.30.F1.M Multifunctional Scale	C32.30.C3.M Multifunctional Scale	C32.60.C3.M Multifunctional Scale
Metrological parameters			
Maximum capacity [Max]	30 kg	30 kg	60 kg
Minimum load	200 g	200 g	400 g
Readability [d]	10 g	10 g	20 g
Tare range	-30 kg	-30 kg	-60 kg
Max readability for non-verified scale	1 g	1 g	2 g
OIML Class	III	III	III
Physical parameters			
Display	5" graphic colour	5" graphic colour	5" graphic colour
Weighing pan dimensions	300×300 mm	700×500 mm	700×500 mm
Packaging dimensions	570×390×170 mm	730×800×270 mm	730×800×270 mm
Net weight	5,3 kg	23,4 kg	23,4 kg
Gross weight	6,6 kg	27,2 kg	27,2 kg
Construction			
Protection class	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator
Construction	mild steel St3S	mild steel St3S	mild steel St3S
Weighing pan material	Stainless steel AISI304	Stainless steel AISI304	Stainless steel AISI304
Communication interface			
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters			
Power supply	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz
Power consumption max.	10 W	10 W	10 W
Optional power supply	internal rechargeable battery	internal rechargeable battery	internal rechargeable battery
Operation time on batteries	operation time up to 5 h	operation time up to 5 h	operation time up to 5 h
Environmental conditions			
Operating temperature	-10 ÷ +40 °C	-10 ÷ +40 °C	-10 ÷ +40 °C

Datasheet

	C32.60.C2.M Multifunctional Scale	C32.150.C2.M Multifunctional Scale	C32.150.C3.M Multifunctional Scale
Metrological parameters			
Maximum capacity [Max]	60 kg	150 kg	150 kg
Minimum load	400 g	1 kg	1 kg
Readability [d]	20 g	50 g	50 g
Tare range	-60 kg	-150 kg	-150 kg
Max readability for non-verified scale	2 g	5 g	5 g
OIML Class	III	III	III
Physical parameters			
Display	5" graphic colour	5" graphic colour	5" graphic colour
Weighing pan dimensions	500×400 mm	500×400 mm	700×500 mm
Packaging dimensions	720×620×210 mm	720×620×210 mm	730×800×270 mm
Net weight	12,8 kg	12,8 kg	23,4 kg
Gross weight	14,8 kg	14,8 kg	27,2 kg
Construction			
Protection class	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator
Construction	mild steel St3S	mild steel St3S	mild steel St3S
Weighing pan material	Stainless steel AISI304	Stainless steel AISI304	Stainless steel AISI304
Communication interface			
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters			
Power supply	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz
Power consumption max.	10 W	10 W	10 W
Optional power supply	internal rechargeable battery	internal rechargeable battery	internal rechargeable battery
Operation time on batteries	operation time up to 5 h	operation time up to 5 h	operation time up to 5 h
Environmental conditions			
Operating temperature	-10 ÷ +40 °C	-10 ÷ +40 °C	-10 ÷ +40 °C

Datasheet

	C32.300.C2.M Multifunctional Scale	C32.300.C3.M Multifunctional Scale
Metrological parameters		
Maximum capacity [Max]	300 kg	300 kg
Minimum load	2 kg	2 kg
Readability [d]	100 g	100 g
Tare range	-300 kg	-300 kg
Max readability for non-verified scale	10 g	10 g
OIML Class	III	III
Physical parameters		
Display	5" graphic colour	5" graphic colour
Weighing pan dimensions	500×400 mm	700×500 mm
Packaging dimensions	720×620×210 mm	730×800×270 mm
Net weight	12,8 kg	23,4 kg
Gross weight	14,8 kg	27,2 kg
Construction		
Protection class	IP 65 construction, IP 43 indicator	IP 65 construction, IP 43 indicator
Construction	mild steel St3S	mild steel St3S
Weighing pan material	Stainless steel AISI304	Stainless steel AISI304
Communication interface		
Communication interface	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi	2×RS232, USB-A, USB-B, Ethernet, 4 IN / 4 OUT (digital), Wi-Fi
Electrical parameters		
Power supply	100 – 240 V AC 50/60 Hz	100 – 240 V AC 50/60 Hz
Power consumption max.	10 W	10 W
Optional power supply	internal rechargeable battery	internal rechargeable battery
Operation time on batteries	operation time up to 5 h	operation time up to 5 h
Environmental conditions		
Operating temperature	-10 ÷ +40 °C	-10 ÷ +40 °C

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.




Extra payment for verification
 

Accessories



- Displays
 Power Adapters
 RS 232 cables (scale - printer)
 Cigarette lighter receptacle power supply cables
 Barcode scanners
 RS 232, RS 485 cables
 Label Printers
 Displays

Software



- E2R System
 Label Editor R02
 R-LAB
- RAD-KEY
 Alibi Reader
 Scales Editor 2.1

Device dimensions


C32.150.C3.M Multifunctional Scale, C32.15.C3.M Multifunctional Scale, C32.60.C3.M Multifunctional Scale, C32.300.C3.M Multifunctional Scale, C32.30.C3.M Multifunctional Scale




C32.C3.K




C32.C3.M




C32.D2





C32.F1.R





C32.F1.M




C32.F1.K




C32.C2.R



C32.C2.K



C32.C2.M



Scale