



PS 8100.5Y.M Precision Balance, PS 10100.5Y.M Precision Balance, PS 4500.5Y.M Precision Balance, PS 3500.5Y.M Precision Balance, PS 2100.5Y.M Precision Balance, PS 6100.5Y.M Precision Balance

More information on the website
radwag.com/en/info,w1,S8H



PS 8100.5Y.M Precision Balance
PS 10100.5Y.M Precision Balance
PS 4500.5Y.M Precision Balance
PS 3500.5Y.M Precision Balance
PS 2100.5Y.M Precision Balance
PS 6100.5Y.M Precision Balance

The drawings, photos and graphics used are for illustrative purposes only.

Functions



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit measurement



Statistics



Checkweighing



IR sensors



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Differential weighing



Ambient conditions monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

Datasheet

	PS 2100.5Y.M Precision Balance	PS 3500.5Y.M Precision Balance	PS 4500.5Y.M Precision Balance
Metrological parameters			
Maximum capacity [Max]	2100 g	3500 g	4500 g
Minimum load	500 mg	500 mg	500 mg
Readability [d]	10 mg	10 mg	10 mg
Verification unit [e]	100 mg	100 mg	100 s
Tare range	-2100 g	-3500 g	-4500 g
Standard repeatability [5% Max]	5 mg	5 mg	5 mg
Standard repeatability [Max]	8 mg	8 mg	8 mg
Standard minimum weight (USP)	10 g	10 g	10 g
Standard minimum weight (U=1%, k=2)	1 g	1 g	1 g
Linearity	±20 mg	±20 mg	±20 mg
Stabilization time	1,5 s	1,5 s	1,5 s
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
OIML Class	II	II	II
Physical parameters			
Leveling system	półautomatyczny - LevelSENSING	półautomatyczny - LevelSENSING	półautomatyczny - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Delivery components	Balance, weighing pan, weighing pan shield, power supply	Balance, weighing pan, weighing pan shield, power supply	Balance, weighing pan, weighing pan shield, power supply
Weighing pan dimensions	195×195 mm	195×195 mm	195×195 mm
Device dimensions			333x206x107 mm
Packaging dimensions	720×370×274 mm	720×370×274 mm	720×370×274 mm
Net weight	7,2 kg	7,2 kg	7,2 kg
Gross weight	9,3 kg	9,3 kg	9,3 kg
Construction			
Protection class	IP 43	IP 43	IP 43
Components and software			
Database capacity	7	7	7
Features of use			
Touch-free operation	2 IR Sensors	2 IR Sensors	2 IR Sensors
Communication interface			
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters			
Power supply	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Balance: 12 – 15V DC 0,8A max	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Balance: 12 – 15V DC 0,8A max	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Balance: 12 – 15V DC 0,8A max
Power consumption	4 W	4 W	4 W
Environmental conditions			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
Ambient conditions monitoring (option)	THBR 2.0 System, THBR BOX, THB P, THB W, THB S	THBR 2.0 System, THBR BOX, THB P, THB W, THB S	THBR 2.0 System, THBR BOX, THB P, THB W, THB S
Storage temperature			-20 ÷ +50 °C
Relative humidity	40% ÷ 80%	40% ÷ 80%	40% ÷ 80%

Repeatability is expressed as a standard deviation from 10 weighing cycles. Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile. 1 Barcode scanners, available as weighing instrument accessory,

communicate with the instrument via RS232 interface exclusively.

Datasheet

	PS 6100.5Y.M Precision Balance	PS 8100.5Y.M Precision Balance	PS 10100.5Y.M Precision Balance
Metrological parameters			
Maximum capacity [Max]	6100 g	8100 g	10100 g
Minimum load	500 mg	500 mg	-
Readability [d]	10 mg	10 mg	10 mg
Verification unit [e]	100 mg	100 mg	-
Tare range	-6100 g	-8100 g	-10100 g
Standard repeatability [5% Max]	5 mg	5 mg	5 mg
Standard repeatability [Max]	8 mg	10 mg	12 mg
Standard minimum weight (USP)	10 g	10 g	10 g
Standard minimum weight (U=1%, k=2)	1 g	1 g	1 g
Linearity	±20 mg	±20 mg	±20 mg
Stabilization time	1,5 s	1,5 s	1,5 s
Adjustment	internal (automatic)	internal (automatic)	internal (automatic)
OIML Class	II	II	II
Physical parameters			
Leveling system	półautomatyczny - LevelSENSING	półautomatyczny - LevelSENSING	półautomatyczny - LevelSENSING
Display	10" graphic colour touchscreen	10" graphic colour touchscreen	10" graphic colour touchscreen
Delivery components	Balance, weighing pan, weighing pan shield, power supply	Balance, weighing pan, weighing pan shield, power supply	Balance, weighing pan, weighing pan shield, power supply
Weighing pan dimensions	195×195 mm	195×195 mm	195×195 mm
Device dimensions	333x206x107 mm	333x206x107 mm	333x206x107 mm
Packaging dimensions	720×370×274 mm	720×370×274 mm	720×370×274 mm
Net weight	7,2 kg	7,2 kg	7,2 kg
Gross weight	9,3 kg	9,3 kg	9,3 kg
Construction			
Protection class	IP 43	IP 43	IP 43
Components and software			
Database capacity	7	7	7
Features of use			
Touch-free operation	2 IR Sensors	2 IR Sensors	2 IR Sensors
Communication interface			
Communication interface	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot	2×USB-A, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters			
Power supply	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Balance: 12 – 15V DC 0,8A max	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Balance: 12 – 15V DC 0,8A max	Adapter: 100 – 240V AC 50/60Hz 0,6A; 12V DC 1,2A Balance: 12 – 15V DC 0,8A max
Power consumption	4 W	4 W	4 W
Environmental conditions			
Operating temperature	+10 ÷ +40 °C	+10 ÷ +40 °C	+10 ÷ +40 °C
Ambient conditions monitoring (option)	THBR 2.0 System, THBR BOX, THB P, THB W, THB S	THBR 2.0 System, THBR BOX, THB P, THB W, THB S	THBR 2.0 System, THBR BOX, THB P, THB W, THB S
Storage temperature	-20 ÷ +50 °C		-20 ÷ +50 °C
Relative humidity	40% ÷ 80%	40% ÷ 80%	40% ÷ 80%

Repeatability is expressed as a standard deviation from 10 weighing cycles. Stabilization time depends on the ambient conditions and the dynamics of weighing pan loading; specified for FAST profile. 1 Barcode scanners, available as weighing instrument accessory, communicate with the instrument via RS232 interface exclusively.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



Accessories

Balance Storage Case
Antivibration Tables
Power Adapters
Cigarette lighter receptacle power supply cables
Additional modules
USB cable (scale - printer)
Professional Weighing Tables
Protective cover for balances
Barcode scanners
RS 232, RS 485 cables

THBR 2.0 System - Ambient Conditions Monitoring
Density determination KIT
Receipt Printer
Fingerprint Reader
RS 232, RS 485 cables
Protective cover for balances
Under-pan weighing
RS 232 cables (scale - printer)
RS 232 – RS 485 Converter

Software

E2R System
Label Editor R02
R-LAB
RADWAG Development Studio

RAD-KEY
RADWAG Remote Desktop
Scales Editor 2.1

Device dimensions

PS 8100.5Y.M Precision Balance, PS 10100.5Y.M Precision Balance, PS 4500.5Y.M Precision Balance, PS 3500.5Y.M Precision Balance, PS 2100.5Y.M Precision Balance, PS 6100.5Y.M Precision Balance

